



1. HTTPS request header
 Request URL
 IP Address
 User Agent String
 Language
 Query string parameters

1. HTTPS request body
 Cookies & Identifiers: [device_id](#) (client_id, app_instance_id), [IDFA](#), [Adid](#), [user_id](#) (optional)
[User properties](#) (optional)
[Events](#) (e.g. views, clicks, purchases, etc.)
[Event parameters](#): (e.g. timestamp, price, currency, etc.)

2. Data owners may use [server-side tagging](#) and owner-managed processing containers for initial web data collection.
3. All HTTPS requests from server-side tagging and MP (#6) to Analytics Collection are routed to general traffic domains.
4. Data collection is routed to the closest available server based on location.
5. Traffic from EU-based visitors (based on IP geo lookup) is routed to [EU-based collection servers](#) for data filtering.
6. MP allows server-to-server interactions, allowing the customer to remove unwanted browser metadata ([GA4 MP](#)).
7. Data filtering occurs in server memory and typically processes and forwards data to US servers within 15 minutes.
8. IP data is only used for geo-location and immediately discarded prior to forwarding to Analytics storage. For EU- based traffic, IP data is discarded from all Google logs and cannot be accessed or used for any additional use cases.
9. This includes regional data collection for [advertising features](#) or [granular location & device data](#).